



Dynamic Engineers Inc.

2550 Gray Falls Dr., Suite#128, Houston, TX, 77077 USA
 TEL: 1-281-870-8822 EMAIL: Sales@DynamicEng.com

H7 LC) ' \$\$6 A!GHF' !(\$A < n!5
 Í ÈÁÈÇÀ { ÀÏ ÖÁÓÛÚÁ

Features and Benefits


- Frequency range: 40MHz
- Supply voltage: 3.3V
- Steady current: 3.5mA Max
- Output waveform: Clipped sinewave
- Frequency stability vs. operating temperature: ± 0.28 ppm
- Phase noise@10KHz: -150dBc/Hz
- Operating temperature: -40°C--+85°C
- Size: 5x3.2x1.85mm


Typical Applications

Stratum 3- Femtocell
 Base Stations

Mechanical Drawing & Pin Connections

Drawing No: MD% \$\$' +!%





Specifications

Specification	Condition	3.3V		Unit
		Min.	Max.	
Supply Voltage Variation (V _{DD})	V _{DD} ±5%	V _{DD} -5%	V _{DD} +5%	V
Frequency Range		40		MHz
Frequency Stability	Overall, 20 Years (Please see below note1)		±4.6	ppm
Frequency Stability Vs Temp. Range	Ref. to (F _{MAX} +F _{min})/2; -40°C--+85°C		±0.28	ppm
Holdover Stability	(Please see below note2)		±0.32	ppm
Supply Current		-	3.5	mA
Output		Clipped Sinewave		
Output Level		0.8	-	Vp-p
Load		10kohm//10pF		
Phase Noise				
100Hz		-120		dBc/Hz
1KHz		-140		
10KHz		-150		
Startup Time		-	5	mSec
Storage Temperature		-55°C--+125°C		

Note1: Including calibration @ 25°C, supply voltage V_{DD}±5% , load ±10%, reflow soldering, 20 years aging and frequency stability over temperature.

Note2: Including 24hours aging, supply voltage V_{DD}±5% and frequency stability over temperature